

Disconnects

Hoff-Trex® Female Flag Disconnects

TPC Wire & Cable's Hoff-Trex® Female Flag Disconnects provide fast and reliable connection and disconnection of two wires by utilizing a 90-degree bend for use in confined spaces. Female Flag Disconnects are available in a variety of options to meet industry requirements spanning automotive, heavy equipment, consumer and industrial applications.



Ratings 300V 600V Maximum Temp 148°C

Engineered to Resist Tension High Temperature

Features & Benefits

Available in Non-Insulated, Partially Insulated, and Insulated; Nylon and Vinyl Options
 Suit the demands of various operations.

Loose, Tape-On-Reel and Metal Strip Options
 Perfect for operations of all sizes.

Color-Coded by AWG Sizes
 Ease of identification.

Solderless
 Ease of use and installation.

High Temp Options
 Perfect for all types of environments.

Ordering Information For complete product ordering information, please scan the QR Code or contact your TPC sales representative

Non-Insulated Male/Female Disconnects			Female Flag Disconnects				
Tab Size (in.)	Female Disconnect	Male Disconnect	Wire Size (AWG)	Tab Size (in.)	Non-Insulated	Nylon Insulated	Metal Strip
0.25 x 0.032	1DF2DM250	2DM1DF250	22-16	0.187 x 0.02	DF22181ST5	FNDF22181ST5	FNDF22181ST5MS
			22-16	0.187 x 0.032	DF22181ST8	FNDF22181ST8	FNDF22181ST8MS
			22-16	0.250 x 0.032	DF22181T	FNDF22181T	FNDF22181TMS
			16-14	0.187 x 0.02	DF18141ST	FNDF18141ST5	FNDF18141ST5MS
			16-14	0.187 x 0.032	DF18141ST8	FNDF18141ST8	FNDF18141ST8MS
			16-14	0.250 x 0.032	DF18141T	FNDF18141T	FNDF18141TMS
			12-10	0.250 x 0.032	DF1210T250	-	-

Insulating Sleeves For Disconnects

Type	Tab Width (in.)	Entry Diameter (mm.)	Part No.
STRAIGHT	0.187	3	KF1830
STRAIGHT	0.25	2.8	KF2528
STRAIGHT	0.25	3.2	KF2532
STRAIGHT	0.25	3.8	KF2538
FLAG	0.187	3	KFF183012M
FLAG	0.187	3.2	KFF1832
FLAG	0.25	3.2	KFF2532
FLAG	0.25	4	KFF2540M
FLAG	0.25	4.8	KFF2548

