

Disconnects

Hoff-Trex® Bullet Connectors

Hoff-Trex® Bullet Connectors are used as a substitute for quick disconnect terminals due to their ability to quickly mate and their reusability. Hoff-Trex® bullet connectors are available in a variety of options to meet industry requirements spanning automotive, consumer and industrial applications.



Ratings



300V

Maximum Temp 75°C

Engineered to Resist

Tension

Features & Benefits

Vinyl Insulated

Suit the demands of various operations.

Loose and Tape-On-Reel Options

Perfect for operations of all sizes.

Color-Coded by AWG Sizes

Ease of identification.

Solderless

Ease of use and installation.

Ordering Information

For complete product ordering information, please scan the QR Code or contact your TPC sales representative

Male Bullet Connectors				Female Bullet Connectors			
Wire Size (AWG)	Diameter (in.)	Vinyl Fully Insulated	Vinyl Fully Insulated Support Sleeve	Wire Size (AWG)	Diameter (in.)	Vinyl Fully Insulated	Vinyl Fully Insulated Support Sleeve
22-16	0.156	AFVGMT5	AFVDGMT5	22-16	0.156	ACVGFT5	ACVDGFT5
16-14	0.156	BVFGMT5	BFVDGMT5	16-14	0.156	BCVGFT5	BCVDGFT5

