

Connectors

Hoff-Trex® Closed-End Connectors

TPC Wire & Cable's Hoff-Trex® Closed-End Connectors offer a quick and reliable connection for wiring harnesses. Crafted from high-quality 6/6 nylon, these connectors feature a reliable tin-plated copper insert. With UL94V2 certification, CSA approval, and RoHS compliance, you can trust in their safety and performance. Available in sizes ranging from 22 AWG to 8 AWG, these connectors are the best choice for secure and versatile connector solutions.

**Ratings**

300V

Standard Option Max Operating Temperature: 105°C

Engineered to Resist

Abrasion



Tension

Features & Benefits**Made from 6/6 Nylon**

Great for resistance to heat.

Resistant to Vibration

Creates a secure connection.

Simple, but Rugged Design

Provide convenient, safe and fast installation.

Available in Sizes From 22 AWG to 8 AWG

Perfect for small and large gauge requirements.

Ordering Information

For complete product ordering information, please scan the QR Code or contact your TPC sales representative

Closed-End Connectors

Part No.	Color	Temp	Voltage	Wire Size
CE100	CLEAR	105°C	300V	22-18
CE100R	CLEAR	105°C	300V	22-18
CE233	CLEAR	105°C	300V	16-14
CE233R	CLEAR	105°C	300V	16-14
CE551	CLEAR	105°C	300V	12-10
CE551R*	CLEAR	105°C	300V	12-10
CE800	CLEAR	105°C	300V	8
CE233HR	WHITE	105°C	300V	16-14
CE551HR	WHITE	105°C	300V	12-10
2218SDB	CLEAR	105°C	600V	22-18
BSDB	CLEAR	105°C	600V	16-14
DSDB	CLEAR	105°C	600V	12-10
8SDB	CLEAR	105°C	600V	8

**Notes**

*Also available in 600V version