

## Connectors

**Hoff-Trex® Open Barrel Connectors**

TPC Wire & Cable's Hoff-Trex® line of open barrel connectors are designed to provide relief from vibration that can cause a wire to fail prematurely. The open barrel utilizes a crimp that creates a low resistance connection between the wire and terminal.

**Ratings**

148°C/300°F Max Operating Temperature

Maximum Electrical Current: 22-16 AWG: 10 Amps

Maximum Electrical Current: 14 AWG: 15 Amps

**Engineered to Resist**

Tension

**Features & Benefits****Tin-Plated Brass**

Improves solderability.

**Open-Ended Design**

Easy Wire Insertion.

**Secure Hold**

Relieves any vibration, providing a longer lasting connection.

**Versatile Connector**

Can be used in various applications and industries.

**Ordering Information**

For complete product ordering information, please scan the QR Code or contact your TPC sales representative

**Maximum Electrical Current: 14 AWG: 15 Amps**

Wire Size	Tab Size (in.)	Non-Insulated
18-14	0.250 x 0.032	LTO61T250N/J
18-14	0.250 x 0.032	LFO61T250N/J

**Maximum Electrical Current: 14 AWG: 15 Amps**

Wire Size	Tab Size (in.)	Non-Insulated Female	Non-Insulated Male
20-14	0.250 x 0.032	LT151T250N/J	LIM51T250N/J

