

Connectors

Hoff-Trex® Releasable Speed-E **Push-In Connectors**

TPC Wire & Cable's Hoff-Trex® lever-type releasable connector is flameretardant and has a transparent polycarbonate shell for easy confirmation of wire insertion. It is available in 2-conductor, 3-conductor and 5-conductor connection styles. These connectors provide easy wire release and are reusable. They're great for appliance wiring, light fixtures, signs and building wire. Hoff-Trex® Releaseable Speed-E Push-In Connectors are for use with rigid/solid and flexible/stranded conductors.











CE Working Temp: 105°C (221°F) Polycarbonate & Polyamide 66, Flame Retardant to UL 94V0

Rated to 600V Maximum for Building Wiring & 1,000V Maximum for Lighting Fixtures & Signs

Engineered to Resist



High Temperature (Laboration Chemicals)



Features & Benefits

Transparent Shell

Allows for easy confirmation for wire insertion.

Compact Size

Perfect for tight spaces.

Accepts conductors up to 12 AWG (18 AWG and larger

solid conductors do not require the operating tool)

Perfect for operations of all sizes and makes for an easier installation.

Reusable Design

Saves the need for excessive inventory and lowers costs.

Ordering Information For complete product ordering information, please scan the QR Code or contact your TPC sales representative

| Part No. | Pack Qty | Wire Positions |
|-------------|-------------------|-------------------|
| RLS-SPEEDE2 | 500/bag 5,000/ctn | 2 |
| RLS-SPEEDE3 | 500/bag 5,000/ctn | 3 |
| RLS-SPEEDE5 | 300/bag 3,000/ctn | 5 |

