

Cable Glands

Sealcon Exios Cable Glands

Sealcon Exios cable glands offer strain relief suitable for hazardous duty locations, dust-tight, high-pressure wash down locations, or even submersible applications.



Ratings

NEMA 4X & 6

IP68/IP69k

V0 to UL94



Deca BDE

Suitable for Class I, II, III, Division 1 & 2

UL 2225

UL 514 B

CSA 22.2

Performance Characteristics

✓ Corrosion Resistant ✓ Liquid Tight Seal ✓ Halogen and Phosphorous-Free ✓ Cold Temperature Rating -25°C

Engineered to Resist



Flexing



Tension



Chemicals

Features & Benefits

Liquid Tight

Submersible to 300 ft., NEMA 4x & 6 (IP68/IP69K).

Highest Pressure Rating

Patented form seal meets 150 PSIG (10 BAR).

Flame-Protected

V0 Rated according to UL 94 Halogen and Phosphorous-Free Materials.

Large Selection

Cable O.D. range from .08" (2 mm) to 3.54" (90 mm).

Non-Corrosive

Resistant to salt water, weak acids, weak alkalis, alcohol, esters, ketones, ether, gasoline, mineral, animal & vegetable oil.

Ordering Information

For complete product ordering information, please scan the QR Code or contact your TPC sales representative

| Raw Brass Part Number | Nickel-Plated Brass Part Number | Fitting Size | Cord O.D. Range (Inches) | Clearance Hole (Inches) |
|-----------------------|---------------------------------|--------------|--------------------------|-------------------------|
| YU13NM-B1 | YU13NM-BR | 1/2" NPT | 0.35-0.63 | 0.83 |
| YU13NL-B1 | YU13NL-BR | 1/2" NPT | 0.49-0.81 | 0.83 |
| YU21NK-B1 | YU21NK-BR | 3/4" NPT | 0.67-1.02 | 1.05 |
| YU29NK-B1 | YU29NK-BR | 1" NPT | 0.87-1.30 | 1.35 |
| YU29LK-B1 | YU29LK-BR | 1-1/4" NPT | 1.10-1.61 | 1.65 |
| YU36NK-B1 | YU36NK-BR | 1-1/2" NPT | 1.10-1.61 | 1.92 |
| YU50NK-B1 | YU50NK-BR | 2" NPT | 1.42-2.07 | 2.375 |
| YU52NK-B1 | YU52NK-BR | 2-1/2" NPT | 1.81-2.57 | 2.875 |
| YU30NK-B1 | YU30NK-BR | 3" NPT | 2.24-3.07 | 3.5 |



Notes

Please contact us for more sizes and configurations.