

Heat Shrink Tubing

Standard Polyolefin Tubing – 2:1 Shrink Ratio

Our Standard polyolefin tubing is designed to protect inline cable components, splices and disconnects. This tubing was designed for jacketing, wire bundles, light duty harnesses and identifying or color-coding wire, cables and terminal components.



Ratings



WW-1 Flame Rating

Temp: -55°C to 125°C

Engineered to Resist



Waterproof



Abrasion



Direct Flame



Chemicals

Features & Benefits

Available in Reels and 4 Ft Sticks

Colors Available are Black, Red, Blue, Yellow, White, Green and Clear

Custom Pieces Available

2:1 Shrink Ratio

Ordering Information

For complete product ordering information, please scan the QR Code or contact your TPC sales representative

Part No.	Inside Diameter (in.)			Reel Qty (ft.)	4 Ft Qty (pcs./pack)
	Min Expanded As Supplied	Max Recovered After Heat	Nominal Recovered Wall Thickness After Heat		
HSTB1/16	0.059	0.026	0.014	500	25
HSTB3/32	0.094	0.039	0.020	500	25
HSTB1/8	0.118	0.059	0.016	500	25
HSTB3/16	0.177	0.091	0.020	250	25
HSTB1/4	0.230	0.118	0.022	250	25
HSTB3/8	0.354	0.177	0.024	200	25
HSTB1/2	0.472	0.236	0.024	200	25
HSTB3/4	0.709	0.354	0.031	100	25
HSTB1	0.984	0.492	0.035	100	25
HSTB1.5	1.575	0.787	0.039	100	-

